

# PRODUCT DATASHEET

## LED TUBE T8 EM VALUE 720 mm 7W 865

LED TUBE T8 EM VALUE | Economic LED tubes for electromagnetic control gear (CCG) and AC mains



### Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Corridors, stairways, parking garages
- Warehouses
- Cooling and storage rooms
- Domestic applications

### Product benefits

- Energy savings of up to 69 % (compared to T8 fluorescent lamp)
- Quick, simple and safe replacement with or without rewiring
- No bending thanks to glass technology
- Very high resistance to switching loads
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Also suitable for operation at low temperatures

### Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires or on AC mains
- Single and tandem operation on conventional control gear ( $\leq 0.9$  m versions)
- Tube made of glass
- Long lifetime up to 50,000 h
- Uniform illumination
- Mercury-free and RoHS compliant
- Type of protection: IP20



- Low flicker according to EU 2019-2020 ( $SVM \leq 0.4$  /  $PstLM \leq 1$ )

---


**TECHNICAL DATA****Electrical data**

|                                                          |                        |
|----------------------------------------------------------|------------------------|
| Nominal wattage                                          | 7 W                    |
| Nominal voltage                                          | 220...240 V            |
| Operating mode                                           | CCG, AC Mains          |
| Nominal current                                          | 33 mA                  |
| Type of current                                          | AC                     |
| Inrush current                                           | 9.2 A                  |
| Suitable for DC input                                    | Yes                    |
| Input voltage DC                                         | 186...260 V            |
| Operating frequency                                      | 50/60 Hz               |
| Mains frequency                                          | 50/60 Hz <sup>1)</sup> |
| Max. lamp number on MCB B10 A                            | 65                     |
| Max. lamp number on MCB B10 A - CCG without compensation | 68                     |
| Max. lamp number on MCB B10 A - CCG with compensation    | 24                     |
| Max. lamp number on MCB B16 A                            | 81                     |
| Max. lamp number on MCB B16 A - CCG without compensation | 85                     |
| Max. lamp number on MCB B16 A - CCG with compensation    | 30                     |
| Total harmonic distortion                                | < 30 %                 |
| Power factor $\lambda$                                   | 0.90                   |

<sup>1)</sup> DC 0Hz

**Photometrical data**

|                                         |                     |
|-----------------------------------------|---------------------|
| Luminous flux                           | 850 lm              |
| Luminous efficacy                       | 121 lm/W            |
| Lumen main.fact.at end of nom.life time | 0.70                |
| Light color (designation)               | Cool Daylight       |
| Color temperature                       | 6500 K              |
| Color rendering index Ra                | 80                  |
| Light color                             | 865                 |
| Standard deviation of color matching    | ≤6 sdc <sub>m</sub> |
| Rated LLMF at 6,000 h                   | 0.80                |
| Flickering metric (Pst LM)              | 1                   |
| Stroboscope effect metric (SVM)         | 0.4                 |



EPREL data spectral diagram PROF  
LEDr 6500K

Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 190 °    |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

Dimensions & Weight



|                                             |           |
|---------------------------------------------|-----------|
| Overall length                              | 734.00 mm |
| Length with base excl. base pins/connection | 720.00 mm |
| Diameter                                    | 26.70 mm  |
| Product weight                              | 110.00 g  |

Temperatures & operating conditions

|                                      |                            |
|--------------------------------------|----------------------------|
| Ambient temperature range            | -20...+45 °C <sup>1)</sup> |
| Maximum temperature at tc test point | 70 °C                      |
| Performance temp. acc. to IEC 62717  | 66 °C <sup>2)</sup>        |

1) Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire  
2) Tp rated. Tp point coincides with Tc point - marked on device

Lifespan

|                                              |         |
|----------------------------------------------|---------|
| Lifespan L70/B50 at 25 °C                    | 50000 h |
| Number of switching cycles                   | 200000  |
| Lumen maintenance at end of service lifetime | 0.70    |

|                                       |        |
|---------------------------------------|--------|
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |
|---------------------------------------|--------|

### Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | G13    |
| Mercury content             | 0.0 mg |
| Mercury-free                | Yes    |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                                              |                 |
|----------------------------------------------|-----------------|
| Energy efficiency class                      | E <sup>1)</sup> |
| Energy consumption                           | 7.00 kWh/1000h  |
| Type of protection                           | IP20            |
| Standards                                    | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG0             |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | LEDTUBE T8 EM V |
|-----------------|-----------------|

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | G13          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | <0.5 W       |
| Claim of equivalent power                           | No           |

|                                                      |            |
|------------------------------------------------------|------------|
| Length                                               | 734.00 mm  |
| Height                                               | 26.70 mm   |
| Width                                                | 26.70 mm   |
| Chromaticity coordinate x                            | 0.313      |
| Chromaticity coordinate y                            | 0.337      |
| R9 Colour rendering index                            | 1          |
| Beam angle correspondence                            | SPHERE_360 |
| Survival factor                                      | 0.9        |
| Displacement factor                                  | 0.9        |
| LED light source replaces a fluorescent light source | No         |
| EPREL ID                                             | 2153802    |
| Model number                                         | AC69483    |

## EQUIPMENT / ACCESSORIES

- Suitable for operation with low-loss and conventional control gears

## Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- Not suitable for emergency lighting.
- Disconnect mains before installation.

## DOWNLOAD DATA

|                                                                                    | Documents and certificates             | Document name                                                          |
|------------------------------------------------------------------------------------|----------------------------------------|------------------------------------------------------------------------|
|  | User instruction / safety instructions |                                                                        |
|  | Extended installation guide            | Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN     |
|  | Extended installation guide            | Notes on the operation of LEDVANCE LED tubes in compensated luminaires |
|  | Extended installation guide            | LEDVANCE Luminaire conversion checklist                                |
|  | Legal information                      | Informationstext 18 Abs 4 ElektroG                                     |
|  | Declarations of conformity             | LED tube                                                               |


| Documents and certificates                                                       |                                     | Document name                               |
|----------------------------------------------------------------------------------|-------------------------------------|---------------------------------------------|
|  | Declarations of conformity UKCA     | LED Tube                                    |
| Photometric and lighting design files                                            |                                     | Document name                               |
|  | IES file (IES)                      | LEDTUBE T8 EM V 720 7W 865 LEDV             |
|  | LDT file (Eulumdat)                 | LEDTUBE T8 EM V 720 7W 865 LEDV             |
|  | UGR file (UGR table)                | LEDTUBE T8 EM V 720 7W 865 LEDV             |
|  | Light distribution curve type polar | LEDTUBE T8 EM V 720 7W 865 LEDV             |
|  | Spectral power distribution         | EPREL data spectral diagram PROF LEDr 6500K |
| Tender texts                                                                     |                                     | Document name                               |
|  | Tender documents                    | LED TUBE T8 EM VALUE 720 mm 7W 865-en       |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854435041 | Sleeve<br>1                  | 775 mm x 28 mm x 28 mm               | 136.00 g     | 0.62 dm <sup>3</sup>  |
| 4099854435058 | Shipping box<br>10           | 810 mm x 170 mm x 100 mm             | 1778.00 g    | 13.77 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

### Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

---

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.