

PRODUCT DATASHEET

Spot Set Recess CCT Adjustable 4.9W CCT 120° Black

LED Spot Set Recess CCT | Recess with integrated CCT LED



Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Highly versatile due to selectable CCT
- Can be rotated and swiveled for optimum illumination
- Through-wiring possible with included connector box
- Easy mounting

Product features

- Recessed ceiling mounting
- Click-CCT version: color temperature adjustable in three steps by repeated switching
- Adjustable swivel angle
- With integrated LED module and driver
- Available with color temperature: 2,700 K, 4,000 K, 6,500 K
- Through wiring possible
- Type of protection: IP20



TECHNICAL DATA

Electrical data


Nominal wattage	4.90 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	42.000 mA
Inrush current	7.5 A
Max. number of luminaires per miniature circuit breaker B16	80
Max. number of luminaires per miniature circuit breaker C10	63
Max. number of luminaires per miniature circuit breaker C16	102
Power factor λ	0.40
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	200 lm
Total luminous flux of contained light sources	420 lm
Luminous efficacy	41 lm/W
Color temperature	2700 K / 4000 K / 6500 K
Reference control setting of contained light source (Kelvin)	2700 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	80
Standard deviation of color matching	6 sdcn
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	120 °

Dimensions & Weight

Diameter	90.00 mm
Height	27.50 mm
Product weight	96.00 g



SPOT SET ADJ 4.9W CCT 120DEG

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20/IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Mounting diameter	75 mm
Mounting depth	40 mm
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from November 2025
----------------	------------------------------

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	Spotlights Adjustable CCT 3x4.9W 827
	Legal information	Legal insert
	Legal information	Safety insert G11222465
	Declarations of conformity	Spotlights
	Declarations of conformity UKCA	Spotlights

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854595769	Folding box 3	94 mm x 202 mm x 103 mm	348.00 g	1.96 dm ³
4099854595776	Shipping box 24	392 mm x 216 mm x 231 mm	3242.00 g	19.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.