

PRODUCT DATASHEET

Essential Orbis IP44 390mm 24W 830 White

Essential Orbis IP44 | Splash-proof LED ceiling light



Areas of application

- Bathrooms
- Workshops, garages, covered outdoor storage areas
- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Long lifetime thanks to LED technology
- Excellent price/performance ratio

Product features

- Type of protection: IP44
- Lifetime up to 30,000 h



TECHNICAL DATA

Electrical data


Nominal wattage	24.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	220.000 mA
Inrush current	0.22 A
Inrush current time T _{h50}	158 µs
Max. number of luminaires per miniature circuit breaker B16	43
Max. number of luminaires per miniature circuit breaker C10	45
Max. number of luminaires per miniature circuit breaker C16	72
Power factor λ	0.50
Total harmonic distortion	64 %
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	1700 lm
Total luminous flux of contained light sources	2700
Luminous efficacy	83 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	6 sdc _m
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

Dimensions & Weight

Diameter	385.00 mm
Height	70.00 mm
Product weight	850.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Metal
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Wall
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	Orbis Essential IP44
	Declarations of conformity	CE Declaration Orbis Essential IP44
	Declarations of conformity UKCA	UKCA Declaration Orbis Essential IP44

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854621529	Bundle 1	70 mm x 390 mm x 390 mm	858.00 g	10.65 dm ³
4099854621536	Shipping box 5	415 mm x 400 mm x 405 mm	5679.00 g	67.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.