

PRODUCT DATASHEET SENSOR CEILING 360DEG IP44 WT

Sensor Ceiling IP44 | Stand-alone motion and light sensors for ceiling mounting



Areas of application

- Indoor
- Stairways
- Basement
- Restrooms

Product benefits

- Sensor for optimized energy savings
- Compact design

Product features

- 2 operating modes selectable (light 6h continous on, switch-on by movement)
- Type of protection: IP44
- Protection class: II




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz

Dimensions & Weight



Product weight	117.00 g
Diameter	92,0 mm
Width	92,0 mm
Height	50.00 mm

Colors & materials

Product color	White
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Capabilities

D	immable	No
Ty	ype of connection	Screw terminal, 3-Pole

Certificates & Standards

Standards	CE / UKCA / EAC
Protection class	II
Type of protection	IP44

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name	
PDF	User instruction / safety instructions	SENSOR CEILING 360DEG IP44	
PDF	PDF Legal information Safety insert G11219301		
PDF	Declarations of conformity	SENSOR CEILING WALL	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854454035	Folding box	100 mm x 100 mm x 74 mm	148.00 g	0.74 dm ³
4099854454042	Shipping box	210 mm x 210 mm x 164 mm	1620.00 g	7.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.