

PRODUCT DATASHEET

SENSOR WALL 180DEG IP55 WT

Sensor Wall 180DEG | Stand-alone motion and light sensors for wall mounting with 180° detection range



Areas of application

- Outdoor
- Corridors, entrance areas
- Garages
- Basement
- Arcade passage
- 180° detection range allowing the sensor to be installed directly next to doorways

Product benefits

- Precise motion detection based on new sensor design

Product features

- 3 operating modes selectable (light 6h continuous on, switch-on by movement or dusk)
- Zero crossing circuit optimized for LED luminaire operation
- Type of protection: IP55
- Protection class: II




TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz

Dimensions & Weight



Product weight	136.00 g
Length	76.00 mm
Width	50.00 mm
Height	91.00 mm

Colors & materials

Product color	White
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Capabilities

Dimmable	No
Type of connection	Screw terminal, 3-Pole

Certificates & Standards

Standards	CE / UKCA / EAC
Protection class	II
Type of protection	IP55

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	SENSOR WALL 180DEG
	Legal information	Safety insert G11219301
	Declarations of conformity	SENSOR CEILING WALL

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854454240	Folding box 1	82 mm x 97 mm x 81 mm	165.00 g	0.64 dm ³
4099854454257	Shipping box 8	204 mm x 174 mm x 178 mm	1641.00 g	6.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.